

PRESERVE™ POLISH, CLEANER, FINISH REJUVENATOR SCRATCH REMOVER TOO

This silicone and wax free product is truly a miracle to say the least. It cleans, polishes and rejuvenates an old finish while removing minor scratches simultaneously.

For best results apply a liberal coat by spray or on a clean, lint-free cotton cloth then wipe thoroughly to clean the surface. To remove scratches, use a fine rubbing pad or 4/0 steel wool in conjunction with this product. Rub the scratched area gently in the direction of the grain. Repeat as necessary until all the scratches are removed. Buff with a clean, lint-free cloth as the final step.



**Improved Formula
with enhanced scratch
removal**

15916	16 oz spray
15908	8 oz
15900	Quart
15901	Gallon

ABRALON® FOAM-BACKED SANDING PADS

A mesh fabric coated with closely sized abrasive particles laminated to foam and a brush cloth backing for easy attachment by grip (velcro). The open mesh and foam construction is ideally suited for use with different types of lubricants including water. The lubricant flows around the abrasive grains and is absorbed or released by the foam as needed for wet sanding and heat sink. Available in 6" foam discs, packaged 20 per box or sold individually.

- Provides a super smooth finish
- Prevents cut-through defects
- No swirl marks
- Prevents cross grain scratches
- Easily conforms to curved and surfaces
- Cuts polishing time by over 50%
- Saves money in abrasives needs



**For a Super Smooth
High Gloss
or Satin Finish**

GRIT	CAT #/Box	Individual Pad
180	241-180	242-180
360	241-360	242-360
500	241-500	242-500
1000	241-1000	242-1000
2000	241-2000	242-2000
3000	241-3000	242-3000 (New)
4000	241-4000	242-4000

RACE GLAZE POLISHING COMPOUND

Polishes your finished surface to a high gloss or wet look. First wet sand with 400 to 4000 grit wet/dry sandpaper or Abralon sanding discs (at right) and our Rubbing Lubricant to level the finish or remove any imperfections.

Wipe with a clean cloth then apply this compound per label directions. Buff with a buffing wheel at 1,500 to 2,000 RPM. **Leaves no swirl marks.**



**Polishing Compound
(leaves no swirl marks)**



Finish off with the Gloss Highlighter to enhance the gloss or get that wet look, or use it to give the furniture a "just-polished" feel and look.

**Gloss Highlighter
(gloss enhancer)**

15192	Polishing Compound	Quart
15200	Gloss Highlighter	Pint

WET SANDING LUBRICANT


A low viscosity, paraffinic oil based wet sanding vehicle and lubricant for all types of finishes. Superior to water and other types due to better heat absorption. Makes for easy clean-up and works equally well with pumice or rottenstone. Excellent for high gloss polishing and, rubbing out with steel wool or scrubbing pad. Leaves no scratch marks. Highly effective for wet sanding with the above Abralon sanding pads. **DO NOT USE for wet sanding between coats, regardless of finish.**



98500	Quart
98501	Gallon

FELT RUBBING BLOCK

Hard, felt block for wet sanding and hand rubbing/polishing of finishes. Please visit our website for further details and utility in rubbing out a finish.
4" x 2" x 1".



53085

COUNTRY WOODCRAFT™ PASTE FINISHING WAX

Without a doubt the finest paste wax on the market. Adds protection and, a hand-rubbed, rich, smooth-feel satin lustre to any finished wood or metal surface. Excellent for use over any stain or finish, solvent or water-based. Formulated with carnuaba wax for added hardness and surface protection. Truly a five star product.

Available in two colors: *natural* for light, tight grain woods; *dark* for open grain, or dark woods. Light color is available in two container sizes; the dark in pint size only.



67470	Natural	Pint Can
67471	Natural	6-Pint Can
67480	Dark	Pint Can

WOL WAX™ - RUB DOWN PASTE CONCENTRATE

Designed for rubbing down a gloss to a satin or "rubbed effect" satin finish, as well as removing imperfections in a finish. Concentrated, water soluble, non-toxic, non-hazardous, biodegradable and silicone free paste. Recoat over with most finishes if desired - no adhesion issues. Excellent for rubbing between coats if high build and depth are needed. Use in with steel wool (3/0 or 4/0) or, a fine scrubbing pad. **Green Technology™ Formula.**

91600	Quart
91601	Gallon



SATIN RUB™ (RUB DOWN LIQUID)

Liquid version of the above WOL-WAX. Ready for use as supplied; does not require thinning.
Green Technology™ Formula.

91630	Quart
91631	Gallon

