

EVERLAST® GYMCOAT™ Eco-Smart™



This high performance, pleasant odor, quick drying, and non-flammable finish fullfills the most demanding requirements in the wood floor coatings industry. **EVERLAST® GYMCOAT™** is elastic, waterproof and able to withstand the wear and abrasion of high foot traffic. By far a more effective and durable finish than a Tung-oil finish from the aspect of cure time, mar and abrasion resistance, drying time, and odor, yet, provides at least an equal if not surpassed richness and beauty to the floor.

Provides a rock hard finish in 24 hours; Tung-oil on the other hand takes thirty (30) days to cure, and Tung-oil doesn't even approach the hardness and mar resistance of the **EVERLAST® GYMCOAT™**.

It is **ecologically friendly** in terms of low VOC and pleasant odor. Dries in about two (2) hours (at 75° F and 45% relative humidity), tack free in about 30 minutes, recoat in 6 hours. Its light straw color enhances the color of the wood grain. It absorbs UV rays into itself, thus protects the wood substrate and stain from UV damage neither Tung-oil or other oil-based finish offer. Resists flaking and chipping and is easy to repair at anytime. Builds fast and usually requires only two coats, plus sealer.

The sealer offers deep sealing of the wood grain thus enhanced durability. The sealer is virtually odorless.

EVERLAST® GYMCOAT™ is also an excellent product for use on outside decking, and generally a couple of coats of the sealer will provided low film build and excellent protection to the wood substrate.

Apply by brush, roller, paint pad, spray, or lambs-wool applicator.

Key Product Benefits

- ✓ Interior/Exterior
- ✓ **Eco-Smart™** with Pleasant Odor
- ✓ Non-Flammable with Low Combustibility Rating
- ✓ Superior Performance and Durability to Tung Oil
- ✓ Superb Durability and Excellent Scuff Resistance
- ✓ No Limit On Number Of Coats Applied
- ✓ Easy Application by Spray Brush, Roller, Paint Pad, or Wipe-On
- ✓ High Build, Usually Requires Only 2 Coats plus Sealer
- ✓ Quick Drying, Reduces Time Between Coats
- ✓ Sanding Between Coats Not Required
- ✓ Blocks UV Rays From Damaging Stain Or Substrate
- ✓ No Plastic Like Appearance
- ✓ Excellent Abrasion Resistance
- ✓ Adheres To Nearly Every Finish For Added Durability or Repair, including UV Coatings
- ✓ Will Not Support Spontaneous Combustion Like Tung Oil

Sheens: Gloss = 94%, Semi-Gloss = 70, Satin = 45%, Dull-Satin = 25%

Solids, by wt.:	50%
Solids by vol.:	46%
Viscosity:	20-25 sec. #4 Ford Cup
Coverage:	Top Coat..... 500-600 sq. ft. per gallon
	Sealer..... 200-300 sq. ft. per gallon
Recoat time @ 75°F, 45% RH:	3 - 4 hours *
Drying time @ 75°F, 45% RH:	Dust free, 30 min.
VOC:	2.29 lbs/gal (275 g/L)

For stain requirements, use our Wiping Wood Stain for best results and color definition. See page 11.



Odorless

	Gloss	Semi-Gloss	Satin	Dull-Satin	Sealer
1 Gal	44101	44201	44301	44601	40501
5 Gal	44105	44205	44305	44605	40505