

RESISTHANE™ PLUS

OPTIMIZED

A Green Technology Formula™ Pre-Catalyzed Wood Lacquer... Cutting-Edge Technology with Unmatched Product Performance!



How RESISTHANE™ Differentiates From Others

- ✓ Green Technology Product Certified
- ✓ Tough and durable with very fast hardness development
- ✓ Extremely environmentally friendly (extremely low VOC)
- ✓ Quick Drying and indefinitely Non-Yellowing
- ✓ Outstanding clarity and depth; none of that plastic look
- ✓ Outstanding warmth and grain definition, like no other
- ✓ Sanding between each coat not a must
- ✓ Ready to spray with excellent flow and leveling
- ✓ Looks superb over stained wood or as a natural finish
- ✓ No catalyst/pot life problem or restrictions
- ✓ Recoat anytime, and no limit on number of coats
- ✓ 100% burn-in when recoated within 48 hours.

Looking to breathe easier and still experience a superior finish?

This internally cross-linked water-based lacquer, with over 30 years of technological innovation into it, is extremely tough and durable with unmatched clarity, depth and richness. No plastic look for sure. **Green Technology™ Formula** certified. Extremely low VOC and very environmentally friendly, including to chemically sensitive individuals. Makes finishing wood safe and easy, by spray or brush. No window of recoatability; recoat at any time with smooth results each time. No need to sand between coats, if so desired. Self-sealing (recommended) or apply over our Clear Wood Sealer (p 14), if so desired. For finishing and refinishing all interior furniture, kitchen cabinets, table tops, office furniture, antiques, and paneling. Safe on children's furniture too. Not recommended for bar tops, restaurant tables, around sink areas - use our **EVERLAST™ Wood Finish** (next page). For flooring application use our **EVERLAST™** or **Green Technology™ GYMCOTE™**, p 16 and 17.

Available in clear in three sheens and in pigmented (black and white) in two sheens plus primer.

Sheens: Gloss = 80, Satin = 45% Dull Satin = 25%

Solids, by wt.:	35%
Solids by vol.:	32%
Viscosity:	25-30 sec. #4 Ford Cup
Coverage:	400 sq. ft. per gallon
Recoat time @ 75°F, 45% RH:	60 minutes
Drying time @ 75°F, 45% RH:	Dust free, 10-15 min.
VOC:	0.5 lbs/gal (60 g/L)

IMPORTANT: Do not use tack cloth between coats. It can cause improper cure, hazing, crazing, lifting or peeling. Use a lint-free cloth, dampened with water only. For same reasons refrain from applying over a slow drying oil based stain. For best results, use our Wiping or Penetrating Wood Stains or HYDROCOTE® Penetrating Stain. Please visit our website for further details on staining issues oil rich wood stains.

"I was very skeptical about using a water-based finish as I needed to switch. Resisthane. is simply fantastic and the best I've ever used and continues as such."

Ron O'Dett
R & R Classic Woodworks

CLEARS

SIZE	GLOSS	SATIN	DULL SATIN
QRT	63200	63300	63300
GAL	63201	63301	63001
5 GAL	63205	63305	63005
55 GAL	63255	63355	63055

PIGMENTED

SIZE	PRIMER		GLOSS		SATIN	
	White	Black	White	Black	White	Black
QRT	92800	58200	54000	53300	54100	53400
GAL	92801	58201	54001	53301	54101	53401
5 GAL	92805	58205	54005	53305	54105	53405



Going
Green

CALL TOLL FREE 1-800-229-0934